

FOCUSSING POWER TO THE POINT

## LDP-VRM 045-12 CA Laser Diode Driver

Rev. 2001



## **Product Description**

The LDP-VRM 045-12 CA is a fast driver for typical single laser diodes. With its high output voltage it is suitable for IR, blue LD's and all kinds of LEDs (no pure resistive load). Depending on the supply voltages output currents of up to 5.0 A can be achieved. The internal DC/DC converter stabilizes the voltage drop across the driving MOSFET to prevent excessive losses.

- Analog modulation dc .. 100 kHz
- Output current: 0 .. 5 A
- High speed
- Adaptive DC/DC converter

## Technical Data\*

Output current (depending on supply voltage)	0 3.4 A @ Uin > 12 V 0 4.5 A @ Uin > 18 V 0 5.0 A @ Uin = 24 V
Max. compliance voltage Current noise	Single laser diode, up to 12 V < 3 %
Current overshoot	< 5 %
Analog modulation (Bandwidth)	Approx. 100 kHz
Current setting input Current monitor	0 5 V 100 mV/A
Trigger	Analog / TTL (jumper)
Supply voltage	12 24 V, min. 3 V above compliance
Power dissipation Dimensions in mm Weight Operating temperature	6 W @ 4.5 A and Uin 12 V 40 x 28 x 20 14 g 0 to +55 °C

\* Specifications measured with a fast recovery diode instead of a laser diode. Technical data is preliminary and subject to change without further notice.

- Innovative current regulation concept actively prevents laser diode from overshoots and overcurrent
- Protection against transients through regulated current rise time
- Adaptive DC/DC converter for lowest losses

Optional Accessories: None

PicoLAS GmbH Burgstr. 2 52146 Würselen Germany

Phone: +49 (0)2405 64594 60 Fax: +49 (0)2405 64594 61